



Rubber Sheet Roll

TECHNICAL DATA SHEET



Rubber Sheet Technical Specification Data

GP Rubber™ will resist most oils, not effected by sunlight or harsh environmental extremes. **GP Rubber™** maintains superior flexibility in hot or cold conditions, and also has the resiliency to maintain mechanical stability under heavy loads. ASTM D2000 tested for light commercial to heavy industrial use for numerous rubber sheet applications.

COLOR:	BLACK
SURFACE:	SMOOTH
TEMPERATURE RANGE:	-30° to 210° F
TENSILE:	950 PSI
DUROMETER:	60A NOMINAL
ELONGATION:	268%

ADHESIVE DATA WHEN APPLIED TO GP Rubber™	
THICKNESS:	5 MILS
SURFACE:	RELEASE LINER 1 SIDE
TEMPERATURE:	-60° to 250° F
COMPOSITION:	ACRYLIC
FDA:	NO

RUBBER SHEET ROLL

PO BOX 171
Shippensburg, PA 17257
Phone: 866.834.8606
Fax: 888.440.5797
E-mail: info@rubbersheetroll.com



www.facebook.com/Rubber-Sheet-Roll

www.twitter.com/rubbersheetroll



Fire Rated: Not Fire Rated | **Chemical Resistance:** Moderate
UV Rated: NO | **Composition:** Polymer Compound